

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



09 JUL 2004

(43) International Publication Date  
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number  
WO 03/058276 A2

(51) International Patent Classification<sup>7</sup>: G01V  
(21) International Application Number: PCT/GB03/00052  
(22) International Filing Date: 9 January 2003 (09.01.2003)  
(25) Filing Language: English  
(26) Publication Language: English  
(30) Priority Data:  
0200560.1 11 January 2002 (11.01.2002) GB

UZ, VC, VN, YU, ZA, ZM, ZW only): WESTERNGECO  
SEISMIC HOLDINGS LIMITED [GB/GB]; PO Box 71,  
Craigmuir Chambers, Road Town, Tortola (VG).

(71) Applicant (for CA only): WESTERNGECO CANADA  
LIMITED [CA/CA]; 24th Floor, Monenco Place, 801 6th  
Avenue SW, Calgary, Alberta T2P 3W2 (CA).

(71) Applicant (for FR only): SERVICES PETROLIERS  
SCHLUMBERGER [FR/FR]; 42, rue Saint Dominique,  
F-75007 Paris (FR).


(72) Inventors; and

(75) Inventors/Applicants (for US only): ROBERTSSON,  
Johan, Olof, Anders [SE/GB]; High Cross, Mading-  
ley Road, Cambridge, Cambridgeshire CB3 0EL (GB).  
STRØMMEN MELBØ, Aslaug [NO/NO]; Sponhog-  
gveien 41B, N-0284 Oslo (NO). VAN MANEN, Dirk-Jan  
[NL/NO]; Schlumberger House, Solbraaveien 23, N-1383  
Asker (NO).

(71) Applicant (for AE, AG, AL, AM, AT, AU, AZ, BA, BB, BE,  
BG, BR, BY, BZ, CH, CN, CO, CR, CU, CY, CZ, DE, DK,  
DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, GR, HR,  
HU, ID, IE, IL, IN, IS, IT, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MC, MD, MG, MK, MN, MW,  
MX, MZ, NL, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,  
SE, SG, SI, SK, SL, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG,

[Continued on next page]

(54) Title: A METHOD OF AND APPARATUS FOR PROCESSING SEISMIC DATA



(57) Abstract: A method determining a calibration filter to calibrate a first component of multi-component seismic data relative to a second component of the seismic data comprises determining the calibration filter from a portion of the seismic data that contains only events arising from critical refraction of seismic energy. The method is particularly suitable for long-offset data, since the first arrival will be a critical refraction event and an automatic picking method may be used. The present invention also provides a wavenumber-dependent calibration filter that is obtained from a calibration filter obtained from data in one offset range and another calibration filter obtained from data in another offset range.

WO 03/058276 A2

BEST AVAILABLE COPY